

AMENDMENTS TO THE CLAIMS:

Please cancel without prejudice claims 4 and 7-11 and amend claims 1, 2, 5, 6 and 12-14 as follows.

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) Light modulating apparatus comprising:

an array of light modulating pixels; and

drive means adapted to drive the array to write a complete image by a weighted bit

a6
cm
plane technique in response to an image signal representing a set of n-digit binary numbers defining the intended intensities of respective pixels of the array, n being an integer greater than one, ~~characterised in that~~wherein the pixels are liquid crystal pixels, and the driving means is arranged to alter the n-digit number in respect of at least one said pixel to a closely adjacent value so that the numbers of 1s and 0s written thereat over said writing of a complete image are brought closer to equality ~~whereby~~to improve thereby improving the dc balance.

2. (Currently Amended) Light modulating apparatus comprising:

an array of light modulating pixels; and

drive means adapted to drive the array to write a complete image by a weighted bit plane technique in response to an image signal representing a set of n-digit binary

numbers defining the intended intensities of respective pixels of the array, n being an integer greater than one, ~~characterised in that~~wherein the pixels are liquid crystal pixels, and over a plurality of successive ~~said~~ complete images the driving means is arranged to alter the n-digit number in respect of at least one said pixel in at least one said complete image to a closely adjacent value so that the numbers of 1s and 0s written at said at least one said pixel over the plurality of images are brought closer to equality ~~whereby to improve~~thereby improving the dc balance.

A6
CMX

3. (*Original*) Display apparatus according to claim 2 wherein said driving means is arranged so that values of said number over said plurality of images provide an average intensity at said at least one pixel substantially equal to the intended intensity.

4. (*Cancelled*)

5. (*Currently Amended*) Display apparatus according to ~~any preceding claim~~one of claims 1-3, wherein said driving means is arranged so that said numbers of 1s and 0s written at said at least one said pixel are brought to equality.

6. (*Currently Amended*) Display apparatus according to ~~any preceding claim~~one of claims 1-3 wherein said driving means includes a look-up table for determining how said at least one number is to be altered.

7. (*Cancelled*)

8. (*Cancelled*)

9. (*Cancelled*)

10. (*Cancelled*)

11. (*Cancelled*)

12. (*Currently Amended*) A method of image signal processing for a weighted bit plane technique, in which an image signal represents a set of n-digit binary number signals each indicative of the intended intensity level of a respective one of a corresponding array of binary pixels, wherein at least one said binary number has an inequality of 1s and 0s, ~~characterised in that~~wherein said method comprises the step of altering the said at least one binary number to a closely adjacent value to at least reduce ~~or remove the~~ said inequality therein and so that any inequality of 1s and 0s in each of the rest of the said set of numbers is left unchanged, reduced or removed.

A6 CMX

13. (*Currently Amended*) A method of writing and displaying an image in response to an image signal representing a set of n-digit binary numbers each indicative of the intended intensity level of a respective one of a corresponding array of binary pixels, a complete image being written using a weighted bit plane technique, the method ~~being characterised in comprising~~ the step that at least one said binary number is altered to a closely adjacent value such that over the writing of said complete image an inequality

of 1s and 0s at the corresponding pixel is at least reduced or removed and so that any inequality of 1s and 0s at pixels for each of the rest of the said set of numbers is left unchanged, reduced or removed.

14. (*Currently Amended*) A method of writing and displaying an image in response to an image signal representing a set of n-digit binary numbers each indicative of the intended intensity level of a respective one of a corresponding array of binary pixels, using a weighted bit plane technique, wherein at least one binary number produces an inequality of 1s and 0s at its pixel over the writing of a complete image, characterised

Abd
Cmto
in thatwherein said method comprises the steps of:

writing a plurality of images each approximating said complete image ~~are written~~ in succession; and

altering the said at least one binary number ~~is altered~~ to a closely adjacent value in at least one of said plurality of images so that over said succession the said inequality of 1s and 0s is at least reduced or removed and any inequality of 1s and 0s at each of the other pixels is left unchanged, reduced or removed.

15. (*Original*) A method according to claim 13 or claim 14 wherein at least one bit plane is refreshed during the writing of a said complete image.